



MATERIAL SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name: ChloraPrep with Orange Tint

Formula: Mixture

MSDS Date of Preparation: February 05, 2010

CareFusion

11400 Tomahawk Creek Pkwy

Leawood, KS 66211

PHONE: (800) 523-0502 FAX: (913) 451-8509

EMERGENCY CONTACT: CHEMTREC 1-800-424-9300

- This number to be used only for spills, leaks, fire, exposure or accidents. Please direct all other inquiries to CareFusion Customer Service at (800) 523-0502.

2. HAZARDS IDENTIFICATION

This product consists of small glass ampule containing a clear, colorless solution of 70% isopropanol and 2% chlorhexidine gluconate and an orange tinted foam pledget inside an applicator. When the ampoule is broken, the solution flows through the pledget and becomes orange in color. This MSDS discusses the hazards of the Chlorhexidine Gluconate/Isopropanol solution in the ampoule and the final tinted product.

EMERGENCY OVERVIEW

WARNING!

Flammable Liquid and Vapor. Causes severe eye irritation. May cause skin irritation. Inhalation of vapors may cause respiratory irritation and central nervous system effects such as headache, dizziness, drowsiness, nausea and unconsciousness. Harmful if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount
Isopropanol (Isopropyl Alcohol)	67-63-0	70%
Chlorhexidine Gluconate	18472-51-0	2%
FD&C Yellow No. 6	2783-94-0	Proprietary

4. FIRST AID MEASURES

Skin: Wash material off the skin with copious amounts of water. If redness or a burning sensation develops, seek medical attention and discontinue use.



Eyes: Flush with copious amounts of water. After initial flushing remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and treated by medical personnel immediately.

Ingestion: Give individual one to two glasses of water to drink. If gastrointestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person)

Inhalation: If symptoms of exposure develop, move to fresh air. Seek medical attention if symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Water fog, alcohol-resistant foam, carbon dioxide or dry chemical. Water spray can be used to cool exposed containers and structures, dilute spills and disperse flammable vapors.

Special Fire Fighting Procedures: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

Unusual Fire & Explosion Hazards: Ampoules may explode if exposed to extreme heat or flame. Vapors are heavier than air and will travel along surfaces to remote ignition sources and flash back.

6. ACCIDENTAL RELEASE MEASURES

For small spills, wipe or mop up and rinse to sewer serviced by a wastewater treatment facility. For large spills, eliminate sources of ignition and ventilate spill area. Wear skin, eye and respiratory protection during cleanup (See Section 8). Soak up liquid with inert absorbent and collect into a suitable waste container. Wash residue from spill area with water and flush to sewer serviced by a wastewater treatment facility if permitted.

7. HANDLING AND STORAGE

Avoid prolonged exposure (ingestion, inhalation, or skin contact). Avoid breathing vapors. Use in well ventilated areas. Keep product away from heat, sparks and flames.

Store in a cool, dry, well-ventilated area away from incompatible chemicals and all sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines:

Isopropanol (Isopropyl Alcohol)	400 ppm PEL-TWA 200 ppm TLV-TWA 400 ppm TWA-STEL
Chlorhexidine Gluconate	None Established
FD&C Yellow No. 6	None Established

(ChlorPrep with Orange Tint) 2 of 5 Pages



Eye Protection: Avoid eye contact. Safety glasses or goggles recommended if eye contact is possible.
Gloves: Latex rubber for limited contact. Butyl rubber or nitrile recommended for prolonged contact.
Respiratory Protection: If the exposure limits are exceeded a NIOSH approved organic vapor respirator appropriate for the form and concentration of the contaminants should be used. Selection and use of respiratory equipment must be in accordance with OSHA 1910.134 and good industrial hygiene practice.
Engineering Controls: Use with adequate general or local exhaust ventilation to maintain exposures below the occupational exposure limits. Use explosion proof equipment where required.

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point:	N/A	Melting Point:	Unknown
Vapor Pressure:	N/A	Specific Gravity:	0.880
Vapor Density:	N/A	% Volatile by volume:	100
Water Solubility:	Complete	Evaporation Rate:	Unknown
pH	7.0 – 7.5	Flash point:	67° F TCC
Flammable Limits:	LEL: 2.0%(isopropanol)	UEL:	12.7% (isopropanol)

Appearance & Odor: Clear, colorless liquid in ampule with orange tinted foam. Product is a orange liquid with an alcohol odor as applied.

10. STABILITY AND REACTIVITY

Stability: Stable

Incompatibility: Oxidizing materials

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Carbon dioxide, carbon monoxide, nitrogen oxides, ammonia, chlorine compounds.

Conditions to avoid: Extreme heat, sparks or flame.

11. TOXICOLOGICAL INFORMATION

HEALTH HAZARDS:

Ingestion: Ingestion may cause mucous membrane and gastrointestinal irritation, abdominal pain, nausea, vomiting, dizziness and drowsiness.

Inhalation: Inhalation of vapors may cause mucous membrane and respiratory irritation and central nervous system depression with symptoms of headache, dizziness and drowsiness.

Eye: Contact may cause severe irritation with redness, tearing and pain with possible eye damage.

Skin: May cause irritation, drying, defatting of the skin. Prolonged contact may cause dermatitis.

Chronic: None known.

Carcinogenicity: None of the components is listed as a carcinogen or suspected carcinogen by IARC, NTP or OSHA.

Medical Conditions Aggravated by Exposure: Employees with pre-existing skin, kidney and respiratory diseases may be at increased risk from exposure.

(ChloroPrep with Orange Tint) 3 of 5 Pages



Acute Toxicity Values:

Isopropanol: Oral Rat LD50 5,045 mg/kg; Inhalation Rat LC50 16,000 ppm/8 hour; Skin Rabbit LD50 12,800 mg/kg
Chlorhexidine Gluconate: Oral Rat LD50 2,000 mg/kg
FD&C Yellow No. 6: Oral Rat LD50 >10,000 mg/kg

12. ECOLOGICAL INFORMATION

Isopropanol: The LC50/96-hour values for fish are over 100 mg/l.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with local, state and federal environmental regulations.

14. TRANSPORT INFORMATION

DOT Information

Proper Shipping Name: Isopropanol Solution

Hazard Class: 3, PG II

UN Number: UN1219

Exemption for US Ground Transport: Consumer Commodity, ORM-D

Exemption for US Air Transport: Consumer Commodity, ORM-D-AIR

Small Quantity Exception: 49CFR173.4

IMO Information

Proper Shipping Name: Isopropanol Solution

Hazard Class: 3, PG II

UN Number: UN1219

Limited Quantity: 1 L/inner receptacle. Limit gross weight - 30 kg/package

IATA Information

Proper Shipping Name: Isopropanol Solution

Hazard Class: 3, PG II

UN Number: UN1219

Packing Instruction: 305

Limited Quantity Packing Instruction: Y305

Alternate Shipping Description: Consumer Commodity, 9, ID8000

Excepted Small Quantities of Dangerous Goods: Class 3, PG II inner limit 30 mL, Outer Package Limit 500 mL



15. REGULATORY INFORMATION

CERCLA: This product is not subject to CERCLA reporting requirements, however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Fire Hazard.

SARA 313: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

16. OTHER INFORMATION

HMIS Rating: Health = 2 Fire = 3 Reactivity = 0

ACGIH:	American Conference of Governmental Industrial Hygienists
IARC:	International Agency for Research on Cancer
OSHA:	Occupational Safety and Health Administration
NTP:	National Toxicology Program
PEL:	Permissible exposure Level (OSHA)
TLV:	Threshold Limit Value (ACGIH)
TWA:	Time Weighted Average over 8 hours
TCC:	Tagged Closed Cup